


SILENT MESSENGER III

*SOL-R-SIGN*TM

SOLAR POWERED
PORTABLE DYNAMIC MESSAGE SIGN

PROCUREMENT SPECIFICATION



LED Solutions

100 Red Schoolhouse Road (A-11)

Chestnut Ridge, NY 10977, USA

Phone: 877-391-0225

www.millenniumvisuals.com

SolarTech, SILENT MESSENGER SOL-R-SIGN, and Control Center 3000 are trademarks of Solar Technology, Inc.

Microsoft, Windows 95, Windows 98, Windows NT, Windows 2000, Windows XP, Windows Vista and other Microsoft products referenced herein are registered trademarks of Microsoft Corporation.

All other brands and product names mentioned herein are used for identification purposes only, and are trademarks or registered trademarks of their respective holders.

This document presents a detailed specification for an small-size solar powered portable dynamic (changeable) message sign. This specification typically requires additions and/or modifications to meet a user's specific requirements.

This specification is subject to periodic revisions as required without notice.

1. General

1.1 Product Description

The **SILENT MESSENGER III** is a solar powered portable dynamic message sign. The **SILENT MESSENGER III** consists of a sign display panel, a supporting structure for the display panel, a photovoltaic array, a battery power supply, an energy management system control unit, and an electronic control console, all mounted on a heavy duty trailer frame.

1.2 Design Objectives

1.2.1 Maximize reliability by using generally accepted design techniques for outdoor-use electrical and electronic equipment.

1.2.2 Minimize operating cost by using a renewable energy source, requiring minimal maintenance.

1.2.3 Maximize safety and effectiveness by using a non-glare, high contrast display panel with long-life expectancy, high-reliability display technology.

1.2.4 Meet or exceed the standards for Portable Changeable Message Signs as listed in the U.S. Federal Highway Administration (FHWA) Manual on Uniform Traffic Control Devices (MUTCD).

1.3 Performance Objectives

1.3.1 Visibility up to 1 mile.

1.3.2 Legibility up to 1/2 mile.

1.3.3 Minimal glare from sunlight and head lights.

1.3.4 Continuous, uninterrupted operation on solar power.

1.3.5 One month minimum, three month typical maintenance interval.

1.4 Quality Assurance Objectives

1.4.1 All manufacturing shall be carried out in a facility with a completely implemented and properly maintained ISO 9001:2000 certified quality management system.

1.4.2 All units shall bear the CE Mark indicating acceptable EMC (Electromagnetic Compatibility) to insure that the units are neither susceptible to nor produce any electromagnetic interference.

1.4.3 Manufacturer shall have a factory authorized service center located within 150 miles of point of delivery. Authorized service center shall receive all units from factory in order to inspect for any shipping damage and verify proper operation prior to final delivery. Delivery directly from manufacturer's facility without inspection by an authorized service center shall not be permitted. Additionally, authorized service center shall be capable of performing warranty service and repairs, and shall provide on-site training on the proper use and maintenance of all equipment delivered.

2. Physical

2.1 Dimensions

- 2.1.1 Length Overall:
- Standard trailer - towing - 112 in. (284 cm)
 - Standard trailer - storage/operational - 112 in. (284 cm)

 - Lift & Rotate trailer - towing - 152 in. (386 cm)
 - Lift & Rotate trailer - storage/operating - 108 in. (274 cm)
- 2.1.2 Width
- 2.1.2.1 Overall :
- Standard trailer - 80 in. (203 cm)
 - Lift & Rotate trailer - 77 in. (196 cm)
- 2.1.2.2 Across fenders:
- Standard trailer - 75 in. (190 cm)
 - Lift & Rotate trailer - 77 in. (196 cm)
- 2.1.3 Height
- 2.1.3.1 Sign in transport position:
- Standard trailer - 92 in. (234 cm)
 - Lift & Rotate trailer - 101 in. (257 cm)
- 2.1.3.2 Sign in operating position:
- Standard trailer - 142 in. (360 cm)
 - Lift & Rotate trailer - 142 in. (360 cm)
- 2.1.4 Ground Clearance:
- All Units - 13 in. (33 cm) (minimum)
- 2.1.5 Weight :
- Standard trailer - 1,182 lbs. (536 kg) (maximum)
 - Lift & Rotate trailer - 2,000 lbs. (907 kg) (maximum)

2.2 Environmental

- 2.2.1 Temperature, operating and storage - -40 to +185 °F (-40 to +85 °C)
- 2.2.2 Relative Humidity - 20% to 98%, non-condensing
- 2.2.3 Wind
- 2.2.3.1 Transport position, maximum trailering speed - 70 MPH (112 KPH)
- 2.2.3.2 Operating position, max. height, outriggers in place - 80 MPH (128 KPH) sustained
- 2.2.4 Electrical Interference - Unaffected by RFI (Radio Frequency Interference) and EMI (Electromagnetic Interference).

3. Trailer Chassis and Sign Support

3.1 Trailer Chassis

3.1.1 Frame Construction

3.1.1.1 Trailer frame shall be constructed of welded 7 Gauge (3/16-inch) CNC formed steel plate and structural steel tubing with either a 3 x 3 x 3/16 inch structural steel tubing receiver, reinforced and welded to the front crossmember (standard trailer) or 7 gauge formed steel plate reinforced and welded to front crossmember for pivoting tongue (lift & rotate trailer).

3.1.1.2 Trailer shall be equipped with a 2 1/2 x 2 1/2 x 3/16 inch structural steel tubing receiver capable of accepting a standard Class II (2) drawbar and hitch pin to accommodate tandem towing. The rear hitch receiver shall be reinforced and welded to a 7 Gauge (3/16-inch) CNC formed steel plate rear cross member. Tandem trailer towing using rear hitch receiver is intended for off road use only and is subject to local laws and regulations!

3.1.1.3 The trailer tongue shall consist of 2 1/2 x 2 1/2 x 3/16 inch structural steel tubing. The tongue shall either bolt into the tongue receiver to facilitate easy removal of the tongue for repair, transportation, or security purposes (standard trailer) or bolt to formed steel plate assembly with an additional removable hitch pin to allow for easy pivoting upward into the storage position (lift & rotate trailer). The trailer tongue shall be equipped with a 2,000-pound capacity swivel-type topwind screw jack with a formed steel footpad (standard trailer only).

3.1.1.4 Trailer frame shall be equipped with tie down points to facilitate securing unit to utility trailer or truck deck for transport.

3.1.2 Suspension

3.1.2.1 Trailer shall be equipped with an independent suspension, torsion-type axle with a 2,200 pound overall capacity. Axle load capacity shall be set at 1,400 pounds nominal.

3.1.2.2 Axle wheel spindles shall be equipped with spindle bearing caps with grease fittings to accommodate wheel bearing lubrication.

3.1.3 Coupler

3.1.3.1 Trailer tongue shall be capable of accepting a 2-inch ball coupler, a 2 1/2-inch (or 3-inch) pintle ring, an optional removable combination coupler, or an optional adjustable height coupler.

3.1.3.2 Trailer shall be equipped with 1/4-inch safety chains with snap-type hooks for secure attachment to tow vehicle hitch.

3.1.3.3 All coupler and safety chain configurations shall comply with SAE J684 standards for Class II (2) trailers.

3.1.4 Surface Preparation and Finishing

3.1.4.1 Trailer chassis and superstructure shall be completely cleaned and deburred prior to finishing. All metal surfaces shall be prepared for finishing using an iron phosphate wash-down process.

3.1.4.2 A polyamide epoxy primer shall be applied to a dry film thickness of 2.5 mils.

3.1.4.3 A high gloss federal safety orange aliphatic acrylic urethane finish shall be applied to a dry film thickness of 2.5 mils.

3.1.5 Lighting

3.1.5.1 Trailer shall be equipped with sealed flush-mounted combination stop, tail and turn lights.

3.1.5.2 Trailer shall be equipped with a lighted license plate holder.

3.1.5.3 Trailer wiring harness shall be completely sealed and water resistant.

3.1.6 Fenders

3.1.6.1 Trailer shall be equipped with unbreakable, molded, solid color, UV-stabilized HDPE (High Density Polyethylene) fenders, completely closed on the inner side to protect trailer frame.

3.1.6.2 Fenders shall be secured to trailer frame with zinc-plated steel thread forming screws and fender washers so as to facilitate easy repair or replacement.

3.1.7 Leveling Jacks

Standard Trailer:

3.1.7.1 Trailer shall be equipped with four telescoping jacks consisting of 2 x 2 inch x 12 gauge perforated galvanized steel tubing equipped with a 3 x 3 x 3/16 inch x 6 inch wide steel foot plate.

3.1.7.2 Jack stands shall be inserted into 2 1/4 x 2 1/4 inch x 12 gauge galvanized steel tubing, welded to the trailer frame at a 45 degree angle.

3.1.7.3 Jack stands shall be locked into position by 3/8-inch zinc-plated steel tab lock pins secured to trailer frame by nylon-coated stainless steel lanyards.

3.1.7.4 Jack stands and tongue jack shall be configured such that unit can be set up on jack stands, level, in operating position, with the trailer wheels raised completely off the ground, permitting removal of wheels and tires for additional security.

3.1.7.5 Jack stands shall be configured such that, when in the operating position, they create a footprint of at least 93 inches, front to rear, and 56 inches, side to side, to provide adequate stability of unit in high winds.

Lift & Rotate Trailer:

3.1.7.6 Trailer shall be equipped with four swivel type screw jacks, minimum capacity rating of 2,000 pounds, mounted at each corner of the trailer frame.

3.1.7.7 The outrigger jacks shall be capable of lifting the trailer frame so trailer wheels and tires can be removed for additional security.

3.1.7.8 Trailer shall be constructed such that the outrigger jacks are protected by 7 Gauge (3/16-inch) CNC formed steel plate guards when the jacks are in the travel position to prevent damage to jacks during transport.

3.1.8 Tires and Wheels

3.1.8.1 Tires shall be B78-13 Load Range C (standard trailer) or ST205/75R14 Load Range C (lift & rotate trailer).

3.1.8.2 Wheels shall be 13-inch x 4 1/2-inch, 5-lug pattern (4 1/2-inch bolt circle), white spoke dress wheel (standard trailer) or 14-inch x 4 1/2-inch, 5-lug pattern (4 1/2-inch bolt circle), white spoke dress wheel (lift & rotate trailer).

3.1.8.3 Wheels and tires shall be sized according to load requirements of trailer and axle.

3.2 Sign Panel Support

Standard Trailer:

3.2.1 Trailer superstructure shall provide complete support of the sign panel in the transport (down) position. Cantilevered support of sign panel is not acceptable!

3.2.2 Trailer superstructure shall be completely assembled with removable fasteners to accommodate quick, easy maintenance and repair.

3.2.3 All fasteners shall be rust resistant and equipped with all metal (stover) lock nuts to prevent loosening of fasteners during normal transportation and operation.

3.2.4 All aluminum to steel attachments shall be made with stainless steel hardware and stainless steel or nylon spacers so as to minimize galvanic corrosion.

3.2.5 Sign Panel Lifting Mechanism

3.2.5.1 Sign panel lifting mechanism shall consist of a 1,000-pound capacity, automatic brake type winch with 1/4-inch wire rope capable of holding the sign panel in any position from full upright to the travel (down) position.

3.2.5.2 Lifting mechanism, through a series of pulleys, shall provide for balanced pull on both sides of sign panel support frame during raising of sign panel into the operate position.

3.2.5.3 Winch shall be zinc-plated to minimize rust and corrosion.

3.2.5.4 Winch shall be designed such that the handle can be removed, for added security, without interfering with the operation of the automatic brake.

3.2.5.5 Sign panel shall be secured in the operating (up) position by two stainless steel, spring-loaded, locking pins.

3.2.6 Trailer superstructure shall provide for support and operation of solar array, with solar array positioned to accommodate charging in both the operating and the traveling positions.

3.2.7 Solar array shall fold flat and flush onto back of sign panel when sign panel is in the transport (down) position so as to minimize wind resistance without the need for an air deflector or spoiler.

3.2.8 Trailer superstructure shall be equipped with a formed steel upper rear crossmember and formed steel upper side members to reinforce the sign panel and solar array support frame.

3.2.9 Trailer superstructure shall be equipped with an integral sighting device, welded in place, to accommodate proper alignment of the sign panel with oncoming traffic, during setup.

Lift & Rotate Trailer:

3.2.10 Sign panel shall be attached to a telescoping mast assembly to facilitate raising and rotating the display panel from the transport position to the operating position safely and quickly by an unassisted operator.

3.2.11 The mast shall consist of a lower assembly and an upper assembly with an electric 12VDC linear actuator mounted inside to provide for raising and lowering the message display panel.

3.2.12 An electric 12VDC linear actuator shall be installed within the sign mast assembly capable of raising the sign panel to the full operating position in less than thirty (30) seconds. The linear actuator shall be equipped with a manual override to permit lowering of the mast in the event of a total loss of electrical power. The linear actuator shall be of a lead-screw and ball drive type equipped with an automatic clutch mechanism to prevent damage to the actuator, mast assembly and sign panel if actuator is operated past the fully raise position, fully lowered position or sign panel assembly is obstructed while being raised or lowered.

3.2.13 Linear actuator shall be easily removable from mast assembly for repair and or replacement without disassembly of mast.

3.2.14 The lower mast shall be fabricated from 4 x 4 x 3/16-inch structural steel tubing inserted through a 5\16-inch steel plate secured to the trailer frame with eight 5\8-inch diameter steel bolts. The lower mast assembly shall be reinforced with 5/16-inch steel gusset plates located below the trailer deck.

3.2.15 The upper mast shall be fabricated from 6 1/2- inch diameter x 3/16-inch wall thickness structural steel round tubing.

3.2.16 The mast assembly shall be equipped with a dual cam locking mechanism located at the bottom of the upper mast. The dual cam locking mechanism shall secure the message display panel in the appropriate viewing position. The locking cam mechanism shall automatically tighten to resist turning in windy conditions. Friction type (disc or band brake) locking mechanisms are not acceptable as slippage can occur in high wind conditions.

3.2.17 The message display panel support mechanism shall be capable of being rotated through 360° and locked into position, at any angle.

3.2.18 The message display panel rotation locking mechanism shall permit the operator to lock the message display into position, safely, at ground level, prior to elevation to full operating height.

3.2.19 The message display panel shall be equipped with a sighting device to facilitate proper alignment during setup.

3.2.20 The upper and lower mast assemblies shall be equipped with nylatron wear pads to provide for smooth easy movement and to avoid metal to metal contact. The message display support mast shall be capable of extended operation without lubrication. Nylatron wear pads shall be adjustable to compensate for normal wear.

3.2.21 Message display panel support structure shall be of non-welded, modular construction to facilitate quick easy repair in the event of accidental damage.

3.2.22 Message display panel shall be secured to a steel superstructure with stainless steel hardware and nylon spacers to minimize the effects of corrosion.

3.2.23 All mounting hardware shall be locking-type.

3.2.24 Heavy gauge steel cradles equipped with rubber bumpers and HDPE wear pads shall securely support sign panel against vertical and lateral movement during transport. No locking pins or latches will be permitted. Sign panel shall automatically lock into the transport position, without operator intervention, when the sign panel upper mast is fully retracted.

4. Message Display Panel

4.1 Dimensions

4.1.1 Width Overall - 80 in. (203 cm)

4.1.2 Height Overall - 47.5 in. (121 cm)

4.1.3 Depth Overall - 6 in. (15 cm)

4.2 Construction

4.2.1 Message Display Panel Case

4.2.1.1 The message display panel case shall be constructed of heavy duty aluminum extrusion secured at each corner by a molded, fiberglass-reinforced plastic corner and black powered coated stainless steel torx head screws and nylon insert locknuts.

4.2.1.2 The back of the message display panel case shall be constructed of aluminum sheet bonded and riveted to the case frame.

4.2.1.3 Interior of message display panel case shall be equipped with extruded aluminum channels to reinforce the display case and to support internal wiring and cables.

4.2.1.4 The display panel case shall be equipped with four breather filter vents, designed to allow the flow of vapor but not fluid, located at the top and bottom of the case frame to provide adequate ventilation to minimize condensation and fogging of the display panel door.

4.2.2 Message Display Panel Door

4.2.2.1 The display panel door shall be constructed of heavy duty extruded aluminum secured at the corners with glass fiber reinforced molded plastic inserts and black powered coated stainless steel torx head screws and nuts.

4.2.2.2 The door shall fit within a flange around the perimeter of the message display panel case frame to provide for a secure weatherproof enclosure.

4.2.2.3 A rubber seal shall be located inside of the flange on the case frame to provide a water tight, dust tight closure.

4.2.2.4 The message display panel shall be enclosed over the display area by a 3/16-inch thick clear UV resistant, scratch resistant, acrylic coated polycarbonate material with a non-glare outer surface to reduce reflection of ambient light and oncoming vehicle head lamps.

4.2.2.5 The polycarbonate material shall be secured in the door frame with an extruded rubber u-channel to provide a cushioned, weatherproof seal.

4.2.2.6 The message display panel door shall be secured in the open position for servicing by a pair of zinc-plated steel telescoping lid supports equipped with automatic latches. The door supports shall be located completely inside of the display panel housing, protected from weather.

4.2.2.7 The display panel door shall be secured in the closed position with adjustable, positive locking, stainless steel draw latches.

4.2.2.8 The message display panel door and case shall be equipped with stainless steel locking hasps capable of accepting standard padlocks to secure the door in the closed position.

4.2.3 Surface Preparation and Finishing

4.2.3.1 Message display panel case and door shall be completely cleaned and deburred prior to finishing. All metal surfaces shall be prepared for finishing using an iron phosphate wash-down process.

4.2.3.2 A wash primer shall be applied to all prepared metal surfaces prior to applying final finish.

4.2.3.3 A matte black acrylic urethane finish shall be applied to a dry film thickness of 2.5 mils.

4.3 Display Characteristics

4.3.1 The message display area shall be approximately 74 inches in width by 41.5 inches in height.

4.3.2 The display area shall consist of a continuous (full) matrix of 48 pixels or dots in width by 27 pixels in height.

4.3.3 The pixels or dots shall consist of two (2) LEDs (Light Emitting Diodes) arranged in a close-spaced pattern so as to produce the appearance of a round image or dot at normal viewing distances.

4.3.4 The display shall color shall be amber (592 nanometer wavelength).

4.3.5 The display shall produce a brightness greater than 10,000 candela per square meter at maximum intensity.

4.3.6 The display shall produce a minimum viewing angle of 24 degrees, with consistent intensity and color across the entire display panel.

4.3.7 The message display shall be capable of displaying one, two, three or four lines of alphanumeric characters or text with a nominal character height ranging from a minimum of 7 inches (27 cm) to a maximum of 30 inches (76 cm).

4.3.8 The message display panel shall be capable of displaying three (3) lines of text with a minimum of eight (8) characters per line, a nominal character height of 10.5 inches and a minimum of three pixels (4 inches / 10 cm) between lines.

4.3.9 The message display shall also be capable of displaying graphic images and symbols using the full 48 pixel width and 27 pixel height.

4.4 Display Modules

4.4.1 Display modules shall be mounted in the sign panel using captive 1/4-turn wing-head fasteners to permit quick, easy module replacement without the need for any tools.

4.4.2 Display modules shall be mounted on rubber cushions to provide shock absorption during transport and to accommodate thermally-induced expansion and contraction of message display panel during operation.

4.4.3 Display module control circuitry shall include a fail-safe device, also know as a watchdog timer, to automatically monitor the performance of the display module and provide a reset / restart command to the on-board microcontroller in the event of any disruption of normal operation.

4.4.4 Display module control circuitry shall be designed to accommodate "hot swapping" - exchange of display modules while sign is operating.

4.4.5 The message display shall consist of an array of identical display modules capable of functioning in any position without the need for switch or jumper setup or special programming.

4.4.6 Display modules and message display panel shall accommodate complete service and exchange of display modules without the need for any tools.

4.4.7 Display modules shall be equipped with locking-type electrical / electronic connectors to provide secure, reliable operation while permitting quick, easy service and repair of message display.

4.5 Cables and Wiring

4.5.1 All message display panel wiring and cables shall be equipped with modular power and signal connectors to permit repairs without the need for any tools.

4.5.2 All power circuit connectors shall use tin or silver plated contacts.

4.5.3 All signal circuit connectors shall use gold plated or gold flashed contacts.

4.5.4 All system wiring, power and signal, shall consist of marine grade wire and cable, with multi-strand, tin-plated conductors.

4.5.5 All power and sign panel signal wiring and cables shall be installed in nonmetallic, flexible, liquid-tight conduits. All conduit fittings shall be installed with rubber sealing rings to maintain liquid-tight characteristics.

5. Main Control Console

5.1 Physical

5.1.1 Control console shall be enclosed in a weather resistant, lockable, molded HDPE (High Density Polyethylene) enclosure secured to the trailer chassis.

5.1.2 Control console shall be completely sealed to accommodate operation in all types of weather.

5.1.3 Control console shall be mounted on heavy duty slides which allow the control console to slide up and pivot into a position convenient to the operator. Slide mechanism shall permit quick, easy removal of control console without the need for any tools.

5.1.4 Control console power and control cables shall include sealed, locking-type connectors to permit quick, easy removal of control console without the need for any tools.

5.1.5 Control console front panel shall consist of a backlit full color LCD (Liquid Crystal Display) with integrated industrial grade touch-screen, sealed and waterproof, to provide a reliable and user-friendly interface for the operator under any weather condition.

5.2 General Operation

5.2.1 Control console shall provide for the complete control of the dynamic message sign, including remote control and radar speed monitoring (when equipped with optional radar speed monitor), without the need for additional hardware, software, external computers or hand-held control devices.

5.2.2 Control console shall include all necessary software to operate the dynamic message sign, including remote control and radar speed monitoring.

5.2.3 Control console, in conjunction with the message display panel, shall have the capability of monitoring and detecting sign panel communication loop failures. In the event of a sign panel communication loop failure, the control console, in the case of soft errors (temporary disruption of message display), shall have the ability to correct the failure immediately and in the case of hard errors (hardware failure), shall have the ability to completely blank the sign panel so as to prevent the display of incorrect, potentially misleading messages.

5.2.4 Control console embedded CPU shall incorporate a soft-core microprocessor design to insure future hardware and software compatibility.

5.2.5 Control console shall be capable of connection to an IBM or compatible desktop or portable (laptop) computer via a standard serial interface (COM) port to facilitate routine service or repair, extensive diagnostics, and the analysis of user files or operating programs.

5.2.6 Control console operating firmware and software shall be field upgradeable with a standard USB flash-drive (memory key).

5.2.7 Full color LCD display shall be equipped with backlighting to accommodate low ambient light level and night time operation. Backlighting shall activate upon any touch-screen activity and remain on for five minutes following the last touch-screen activity.

5.2.8 Main power to the sign panel and the control console shall be controlled by a combination switch and circuit breaker in order to provide electrical protection without the need for fuses.

5.3 Programming

5.3.1 Control console shall provide an intuitive icon-driven graphical user interface (GUI) along with step by step instructions to the operator, via the front panel, as the various programming functions are performed, for simple easy programming and operation. On-screen help files shall be included.

5.3.2 Control console shall be capable of storing all messages in alphabetical order by the first letter of the first word of the name assigned to the message to permit quick recall of messages without the need for maintaining a numeric listing of pages and messages. Pages and messages shall be automatically sorted any time pages and/or messages are added to or deleted from the library. Because of difficulty in locating and retrieving stored pages and messages, number coded storage of pages and messages shall not be permitted.

5.3.3 Control console shall accommodate a minimum of fifty (50) full alphanumeric passwords each providing one of four levels of access to various control console functions. Each password shall allow access to only the functions required by that particular dynamic message sign operator. The four levels of access are as follows:

Quick-Picks	Select from six (6) pre-programmed messages with no programming required. Simply touch a message for display. No access to any permanent data files.
User Menu	Create, Edit, Delete, Save, Display, and Schedule messages. Create, Assign and Edit Quick-Picks. Check System Status and perform basic diagnostics.

Supervisor Menu	All User Menu Functions. Create and delete Quick-Picks and User passwords. Set system operating parameters.
Administrator Menu	All Supervisor Functions. Create and delete Administrator and Supervisor passwords. Set controller operating parameters.

5.3.4 Control console shall be capable of displaying message on the message sign display panel during such time as the operator may be adding, editing or deleting pages and messages from the control console user files. Blanking of the message sign display panel during normal operator activity is strictly forbidden.

5.3.5 Control console shall be capable of monitoring ambient light conditions and making appropriate adjustments to the intensity of the sign panel display to maintain acceptable display contrast throughout changing ambient lighting conditions. The control console shall provide a minimum of ten (10) intensity levels between minimum and maximum display brightness.

5.3.6 Control console shall be equipped with a real time clock and calendar feature to accommodate automatic, unattended changing of messages at predetermined days and times.

5.3.7 Control console shall provide special function icons to provide access to common user functions in a single step.

5.3.8 Control console shall be capable of storing a minimum of 500 messages, each message capable of accommodating a minimum of 100 pages.

5.3.9 Control console shall be capable of page display times from 0.1 seconds to a minimum of 99 seconds in 0.1 second increments.

5.3.10 Control console shall be capable of displaying messages, during message creation, editing or selection, exactly as they will appear on the message display panel.

5.3.11 Control console shall permit the editing of messages that are currently being displayed, showing the revised message as soon as message editing has been completed.

5.3.12 Control console shall accommodate the creation and editing of graphic images, the addition of graphics to existing text messages, and the modification of existing graphic images to be saved under a new graphic image name.

5.3.13 Control console shall provide a selection of standard highway work zone sign graphic images, fixed left and right arrow images, moving or sequential left and right arrow images, and moving or sequential left and right chevrons.

5.3.14 Control console shall provide the capability to display battery bank voltage to 0.1 Volt accuracy directly on the control console display.

5.3.15 Control console shall provide for a user selectable low-battery-voltage caution message when the battery voltage drops to a user specified level (above the low-battery automatic shut down voltage). The low-battery-voltage caution message shall be user programmable by an operator with a supervisor level password.

5.3.16 Control console shall be NTCIP compatible supporting, at a minimum, the ability to display messages sent over a network type connection using standard NTCIP commands.

6. Power System

6.1 General

6.1.1 Operating Voltage - 12 Volts DC nominal

6.1.2 Operating Energy Requirement - 40 Amp Hours per day nominal (maximum) at Spring or Fall Equinox (i.e. 12 hours of daylight, 12 hours of darkness)

6.1.3 Main Power Switch - Main power switch shall be a combination switch and electromagnetic, thermal circuit breaker to provide complete electrical system protection without the inconvenience of conventional fuses. Main power switch shall be splash proof and weather resistant.

6.2 Battery Bank

6.2.1 Number of batteries - Specify two (2), four (4) or eight (8)

6.2.2 Battery type - 6-Volt, heavy duty, deep cycle - specify - flooded lead-acid or gel-cell

6.2.3 Energy capacity - 600 Amp Hours nominal (4 batteries). Sufficient energy capacity to operate the message sign, displaying typical three-line normal size character messages for 14 days, without any energy input from the solar array.

6.2.4 Battery / Equipment Compartment(s)

6.2.4.1 Battery / Equipment Compartment(s) shall be constructed of molded HMWPE (High Molecular Weight Polyethylene), color impregnated with Federal Safety Orange with 0.5% UV stabilizer added to prevent fading.

6.2.4.2 Compartment(s) shall be designed to completely contain spills from a failed or damaged battery case.

6.2.4.3 Compartment(s) shall be capable of supporting an operator standing on top of the battery / equipment compartment to service unit.

6.2.4.4 Compartment(s) shall be designed such that the lid automatically latches in the closed position and holds the batteries in place. Lid shall be capable of being locked in the closed position with a standard padlock.

6.2.4.5 Lid shall be secured to compartment by an integral plastic hinge that permits the lid to be completely removed from the compartment for service. Lid on the compartment containing the control console shall be automatically supported in the open position by a telescoping lid support.

6.2.4.6 Compartment(s) shall be designed to provide adequate ventilation for the batteries during charging yet prevent the ingress of water during use or transport.

6.2.4.7 Compartment(s) shall be capable of housing four (4) BCI Group GC-2 batteries.

6.3 Solar Array

6.3.1 Photovoltaic module type - Single crystal (monocrystalline) silicon

6.3.2 Number of solar cells per module - 36

6.3.3 Solar array power output - specify - 150, 225, or 300 Watts peak

6.3.4 Entire trailer (standard trailer) or Solar Array (lift & rotate trailer) shall tilt, with sign panel in the down or transport position to allow for fast, easy cleaning and maintenance of the solar array.

6.3.5 Solar array energy output shall be sufficient to operate the changeable message sign, under normal operating conditions, with the solar array in a flat, horizontal position. It shall not be necessary to tilt or rotate the solar array to provide sufficient energy output from the solar array to operate the message sign continuously.

6.3.6 Photovoltaic module junction boxes shall be equipped with watertight strain reliefs at all cable entry points.

6.4 Wiring and Cabling

6.4.1 All power and control wiring and cables shall be in nonmetallic, flexible, liquid tight conduits.

6.4.2 All conduit fittings shall be sealed at bulkheads or enclosure entry points.

6.4.3 All wiring shall be marine grade, multi-strand, tin-plated copper with PVC insulation rated for outdoor use.

6.4.4 All power system wire terminals shall be tin-plated copper to minimize the effects of galvanic corrosion.

6.4.5 Main power wiring shall be 10 AWG minimum.

6.4.6 Battery terminations shall consist of 5/16-18 UNC marine stud with stainless steel split lock washer and hex nut with 5/16 tin-plated copper ring terminal.

6.4.7 Solar panel terminations shall consist of stainless steel screws with #8 tin-plated copper snap spade terminal.

6.4.8 All other terminations shall consist of locking-type quick-disconnect connectors with tin-plated terminals for power connections and gold-plated terminals for signal connections. Terminal strips, screw or compression type, shall not be permitted

6.5 Energy Management System

6.5.1 Solar energy management system control unit shall include a completely solid state charge controller capable of operating in an outdoor environment. No mechanical or electromechanical switching to control charging current is permitted.

6.5.2 All wiring connections to the energy management system control unit shall be made with locking-type multi-pin connectors to facility quick, easy servicing of the control unit without the need of any tools. Electrical connections shall include an auxiliary 12-Volt power connection to provide power for accessory devices.

6.5.3 Energy management system control unit shall monitor solar array voltage, solar array current, battery voltage, battery current and ambient temperature.

6.5.4 Energy management system control unit shall regulate energy flow from the solar array into the battery bank based on ambient temperature so as to avoid over charging of the batteries and minimize the consumption of electrolyte.

6.5.5 Energy management system control unit shall provide for the controlled periodic pulsing of the solar array current to assist in minimizing sulfate deposit buildup on the battery plates.

6.5.6 Energy management system control unit shall provide for remote monitoring of the battery bank voltage, at the terminals of one of the batteries, to assist in optimizing the transfer of power into the battery bank.

6.5.7 Energy management system control unit shall be equipped with a 2-line by 16-character LCD (Liquid Crystal Display) displaying sequentially, solar array voltage, solar array current, battery voltage, and battery current. In addition, the energy management system control unit shall display a low battery voltage warning message whenever the battery bank voltage drops below 10.9 Volts.

6.5.8 Energy management system control unit shall automatically switch current to the message sign off whenever the battery bank voltage drops below 10.7 Volts to prevent damage to the battery bank due to over-discharging the batteries.

6.5.9 Energy management system control unit shall provide for automatic reverse polarity protection, including reverse polarity indicator lamps, for the solar array and the battery bank.

6.5.10 Energy management system control unit shall provide for automatic fault protection without the need for fuses. The use of fuses for fault protection shall not be permitted.

7. Documentation

7.1 Operation and Maintenance Manual

7.1.1 Setup and Operation

7.1.2 Programming

7.1.3 Maintenance

7.1.4 Troubleshooting and Repair

7.1.5 Assembly Diagrams and Parts Lists

7.1.6 Specifications

7.1.7 Appendix

7.2 Control Center 3000 for Windows - Users Manual

7.2.1 Installation and Setup

7.2.2 Control Center Operation

7.2.3 Appendix

7.3 User Guide

7.3.1 Pre-transport checklist.

7.3.2 Job site setup checklist.

7.3.3 Basic programming instructions.

7.3.4 Basic system status evaluation.

7.3.5 Weatherproof card attached to unit with nylon-coated stainless steel lanyard.

8. Maintenance

8.1 Scheduled Maintenance

8.1.1 Solar Array - Clean with water and mild detergent as needed.

8.1.2 Battery Bank - Check electrolyte level once each month and add distilled water as needed.

8.2 Preventive Maintenance

8.2.1 Inspect and lubricate axle hubs once per year.

9. Warranty

9.1 Standard Warranty

9.1.1 Bumper to Bumper - Full warranty, parts and labor - One year

9.1.2 Electrical and Electronic Components, Control Console - Two years

9.1.3 Display Modules

9.1.3.1 Standard - Three years

9.1.3.2 Mega-Flux - Five years

9.1.4 Solar Panels - Ten years

9.2 Extended Warranty - Consult factory

10. Options

10.1 Battery Charger

10.1.1 Charger type - Switching regulator, constant voltage with automatic switch to maintenance or trickle charge.

10.1.2 Input Voltage - 110 VAC 50/60 Hz

10.1.3 Available models with typical recharge times.

10.1.3.1 30-Amp - 36 hours (8 batteries), 18 hours (4 batteries)

10.1.3.2 45-Amp - 24 hours (8 batteries), 12 hours (4 batteries)

10.1.3.3 75-Amp - 16 hours (8 batteries), 8 hours (4 batteries)

10.1.4 Battery charger unit shall install in the field with minimum effort.

10.2 Remote Control

10.2.1 General

10.2.1.1 The remote control option shall provide for complete control of all dynamic message sign functions. The remote control option shall, at a minimum, provide for:

- Sending a message to a remote PCMS for immediate display.
- Receiving the message currently displayed on a remote PCMS.
- Managing the message libraries and message schedules on a remote PCMS.
- Checking the operating status, including battery voltage and ambient light level of a remote PCMS.
- Operate and maintain a minimum of 100 remotely located message signs.

10.2.1.2 Data rate - 10/100 Base-T Ethernet

10.2.1.3 Communication Protocol - Proprietary with complete CRC error detection and correction.

10.2.1.4 Data Format - Data is encrypted and compressed for added security and reliability.

10.2.1.5 All operating software for message sign control console and host computer shall be included with basic message sign package.

10.2.1.6 Remote control system shall install in the field with minimum effort.

10.2.2 Remote control of any networked (IP addressable) PCMS may be achieved from any host computer with internet connectivity (either with standard NTCIP commands via SNMP or STMP, or with Control Center 3000). Remote control software (Control Center 3000) shall be provided free of charge with unit and function on any host computer, independent of operating system. Control console and remote control software shall incorporate a challenge/response encrypted type password security system to prevent unauthorized access of any networked PCMS.

10.2.3 Cellular Transceiver Operation

10.2.3.1 Wireless modem with up to a 3-Watt cellular transceiver.

10.2.3.2 MNP 2-4 Error Control - Automatic error detection and correction.

10.2.3.3 MNP 5 Data Compression - Higher data rates, shorter connection times.

10.2.3.4 MNP 10EC - Enhanced performance over noisy cellular connections.

10.3 Radar Speed Monitor

10.3.1 General

10.3.1.1 Operating Frequency - 24.15 GHz (K-Band)

10.3.1.2 Antenna Beamwidth - 12^o (Circular Pattern)

10.3.1.3 Capture Angle - 16.5^o typical (Circular Pattern)

10.3.1.4 Target Speed Range - 12 to 125 MPH (20 to 200 km/h)

10.3.1.5 Target Speed Accuracy - 1 MPH typical

10.3.1.6 Detection Distance - 1500 Feet (Automobile-size target)

10.3.1.7 Radar unit shall install in the field with minimum effort.

10.3.1.8 Message sign shall be pre-wired and pre-programmed for radar speed monitor option.

10.3.2 Operating Features

10.3.2.1 Target Speed Display - The speed of the target can be displayed as part of any user-created messages, in any character size, in any position in the message. Multiple messages which include target speed can be stored in the message library for use in multiple sequences.

10.3.2.2 Triggered Display - A sequence can be displayed only when an acquired target exceeds a preset speed threshold. This sequence can include the display of the target speed. If no target is acquired or if the acquired target is below the preset threshold, the default or continuous sequence will be displayed. Default sequence can be a blank display.

10.3.2.3 Window Triggered Display - Upper and lower speed thresholds can be preset so the special sequence is displayed only when the target speed is above the lower threshold but below the upper threshold. This sequence can include the display of the target speed. If no target is acquired or if the acquired target is above or below the preset thresholds, the default of continuous sequence will be displayed. Multiple windows can be programmed each with a different sequence to be displayed when the acquired target speed is above the minimum speed but below the maximum speed threshold for that particular window. Each of these sequences can include the display of the target speed.

10.3.2.4 All necessary software features shall be included with the basic message sign package.

- This Page Intentionally Left Blank -